



# Reference Formula

Sample preparation date: YYYY/MM/ZZ

## PERFORMA SW-76 消融霜

EP-SC-CWO-0051A\_V1

Description: A melting cream upon contact with the skin, presenting a cottony thickness on the surface, yet delivering a refreshing sensation. **PERFORMA™ SW-76 Synthetic Wax** achieves the thickness characteristic of a cream while remaining light and non-sticky, contributing to a more stable emulsion.

### FORMULA

Phase	Ingredient (Trade Name)	Ingredient (INCI Name)	% By Weight	Function
O1	<b>PERFORMA™ SW-76 Synthetic Wax<sup>9</sup></b>	<b>Synthetic Wax</b>	<b>4.00%</b>	Thickener (Oily)
	<b>ES-5300 Formulation Aid<sup>1</sup></b>	<b>Lauryl PEG-10 Tris(trimethylsiloxy)silylethyl Dimethicone</b>	<b>0.30%</b>	Emulsifier
	<b>ES-5612 Formulation Aid<sup>1</sup></b>	<b>PEG-10 Dimethicone</b>	<b>0.70%</b>	Emulsifier
	<b>FB-9586 Silicone Elastomer Blend<sup>1</sup></b>	<b>Cyclopentasiloxane (and) Dimethicone / Vinyl Dimethicone Crosspolymer (and) Dimethicone</b>	<b>6.00%</b>	Skin feel
	<b>2502 Cosmetic Fluid</b>	<b>Cetyl Dimethicone</b>	<b>4.00%</b>	Skin feel
	IDD	ISODODECANE	4.00%	Skin feel
	<b>PMX-0345 Cyclosiloxane Blend<sup>1</sup></b>	<b>Cyclopentasiloxane (and) Cyclohexasiloxane</b>	<b>3.00%</b>	Skin feel
	<b>ERCAREL TCC V<sup>14</sup></b>	<b>Caprylic/Capric Triglyceride</b>	<b>15.19%</b>	Skin feel modifiers
W1	D.I Water	D.I Water	up to 100	
	<b>TILAMAR® PDO<sup>2</sup></b>	<b>Propane-1,3-diol</b>	1.12%	Pigment
	NaCl	Sodium chloride	1.12%	Pigment
A	Preservative	Preservative	q.s	Preservative

Suppliers: 1. Dow ;2.DSM ;9. Nu Cera; 14. ErcaWilmar

### PROCEDURE

Recommendations contained, herein this Reference Formula, are advisory only.

4F-3, No. 100, Sec. 1, Jia Feng 11th Rd., Chupei, Hsin-Chu Hsien 30273, Taiwan, R. O. C.

TEL No. : 886-3-657-9279 FAX No. : 886-3-657-9278

Website : [www.essence-plus.com](http://www.essence-plus.com) E-MAIL : [service@essence-plus.com](mailto:service@essence-plus.com)





# Reference Formula

Sample preparation date: YYYY/MM/ZZ

1. Prepare Phase W1 and O1 separately, and heat to 75-80 °C.
2. Add Phase W1 to O1 under stirring until homogenizing.
3. Add Phase A into the main tank after cooling (<40 °C).
4. Mix well.

*The information given in this publication is based on our current knowledge and experience and maybe used at your discretion and risk. It does not relieve you from carrying out your own precautions and tests. We do not assume any liability in connection with your product or its use. You must comply with all applicable laws and regulations and observe all third party rights.*

**Recommendations contained, herein this Reference Formula, are advisory only.**

4F-3, No. 100, Sec. 1, Jia Feng 11th Rd., Chupei, Hsin-Chu Hsien 30273, Taiwan, R. O. C.

TEL No. : 886-3-657-9279 FAX No. : 886-3-657-9278

Website : [www.essence-plus.com](http://www.essence-plus.com) E-MAIL : [service@essence-plus.com](mailto:service@essence-plus.com)

